



**ATOLI**  
愛托力

愛托力有限公司 *ATOLI MACHINERY CO.,LTD.*  
承通有限公司 *NEW CHAIN-TONGS CO.,LTD*



技術研發、專業生產、品質保證



ISO-9001  
Certificated

CE

<http://www.atoli.com>



**ATOLI**  
愛托力  
SINCE 1974

## 携帶式磁性鑽台 Magnetic Drilling Machine

技術研發、專業生產、品質保證



型號 Model	AI-20C	AI-25C
額定馬力輸出 Rated output	1500W	1600W
電壓 Rated Voltage	110/220V	110/220V
空轉 No-load speed	350R.P.M	300R.P.M
鑽孔規格 Drill specification	MT 2麻花鑽頭 Twist Drill	MT 3麻花鑽頭 Twist Drill
最大鑽孔能力 Max. Drill Dia.	20mm	25mm
磁鐵尺寸 Magnet dimensions	200x105x65m/m	200x105x65m/m
最大深度 Max. depth	180mm	180mm
磁鐵吸持動力 Magnet holding power	13000N	13000N
重量 N.W.	20.4KG	20.9KG



AI-45C



AI-50C



型號 Model	AI-45C	AI-50C
額定馬力輸出 Rated output	1600W	1500W
電壓 Rated Voltage	220V,380V,415V / 3 Phase	110/220V
空轉 No-load speed	160R.P.M	350R.P.M
鑽孔規格 Drill specification	MT 4麻花鑽頭 Twist Drill	Φ 19m/m深孔穴鑽 Hole Cutter
最大鑽孔能力 Max. Drill Dia.	45mm	50mm
磁鐵尺寸 Magnet dimensions	254x122x70m/m	200x105x65m/m
最大深度 Max. depth	260mm	180mm
磁鐵吸持動力 Magnet holding power	16500N	13000N
重量 N.W.	41.6KG	21.9KG

**專業品質 追求卓越**  
The specialized quality pursue is remarkable



携帶式半自動磁性鑽台  
(Automatic Magnetic Drilling Machine)



**配件：**

1. ATOLI刀削油精一罐。
2. 六角板手一組。
3. 中心頂針長、短各一支。
4. 說明書一份。
5. 德式T型板手一支。

**Accessories:**

1. ATOLI Cutter oil: 1pc.
2. Hex Spanner: 1 set.
3. Center long and short size each: 1pc.
4. User's Manual: 1 copy.
5. German-type T-spanner: 1pc.

型號 Model	馬達 Motor			鑽孔能力 Hole-cutting capacity			磁鐵尺寸 Magnet dimensions	磁鐵吸持動力 Magnet holding power	重量 N.W.
	額定馬力輸出 Rated output	電壓 Rated Voltage	空轉速度 No-load speed	鑽孔規格 Drill specification	最大鑽孔能力 Max. Drill Dia.	最大深度 Max. depth			
ATT-55N	1500W	220V	350R.P.M	φ19mm深孔六鑽 Hole Cutter	55mm	>100mm	200x92x53mm	13000N	24 KG

1. 磁性鑽臺體積小、功率大、定位準確、輕巧靈活攜帶方便。
  2. 穴鑽冷卻方式可經由刀軸內部噴冷卻液。
  3. 觸摸開關，在冷卻液少量潑濺的情況下不會燒壞內部控制綫路。
  4. 導版上下升降滑道內嵌2根銅條，阻力更小，操作更靈活且耐用。
  5. 權威機構檢測實際功率已經達到1500W，能滿足長時間的作業。
  6. 無需人力手動操作，能減少刀刃磨損率，堅固耐用，無故障率！
1. Magnetic drill stand's volume is small, frequency is big, location is accurate, light & handy, carry conveniently.
  2. Hole cutters' cooling method is through the inside of cutter spindle to spray cooling liquid.
  3. Touch switch, when cooling liquid is splashed few, it will not burn the inside control circuit.
  4. Guide plate Rising & Descending slide inside is inserted 2 pcs copper strip, resistance is much smaller, operation is much more handy & durable.
  5. Authoritative institution inspects and tests the real frequency, it has achieved 1500W, it can satisfy long time operation.
  6. Overload stop detection system helps prevent motor and cutter damage

公司：台中市南區學府路91號

Office : 91, Hsioh Fu Rd., South Dist, Taichung City, Taiwan

TEL:+886-4-22870860(4線) FAX:+886-4-22860876

Http://www.atoli.com E-mail:sales@atoli.com

工廠：台中市大里區東興路535巷6弄6號

Factory : 6, Alley 6, Lane 535, Tung Hsing Rd

Dali Dist, Taichung City, Taiwan

TEL:+886-4-24060830 FAX:+886-4-24064187

E-mail:atoli@atoli.com